

भा.कृ.अनु.प.–केन्द्रीय आलू अनुसंधान संस्थान
शिमला – 171 001 (हि0 प्र0)

स्पीड पोस्ट

एफ सं0 02–133 / 2016 / स्था–2 /

दिनांक: 20 जून, 2016

सेवा में,

विषय : Repair of sewer line and retaining wall of Type-III (C-Block) at Green Park colony
Khalini, Shimla-reg.

महोदय,

उपरोक्त प्रस्तावित कार्य (जिसका विवरण संलग्न है) के क्रियान्वन हेतु निम्न निबंधन व शर्तों पर निविदा/कोटेशन आमंत्रित की जाती है।

1. कोटेशन मोहरबंद लिफाफे में कार्य का नाम व नियत तिथि लिख कर **प्रशासनिक अधिकारी (स्था–2), के.आ.अ.सं., शिमला, हि.प्र.** के नाम डाक द्वारा अथवा स्थापना अनुभाग में रखे Tender Box में डाली जा सकती है।
2. कोटेशन/निविदा ठेकेदार के लैटर पैड अथवा संलग्न (Annexure-I) के साथ हस्ताक्षरित/मोहर सहित भेजी जानी चाहिए।
3. कोटेशन इस कार्यालय में दिनांक **11.7.2016 को दोपहर 2.30 बजे** तक अवश्य पहुंच जानी चाहिए जिन्हें उसी दिन **सांय 3.00 बजे** खोला जाएगा। निर्धारित समय/तिथि के बाद प्राप्त कोटेशनों पर विचार नहीं किया जाएगा।
4. किसी भी प्रकार की कटिंग और ओवर राइटिंग होने की स्थिति में उसके साथ लघु हस्ताक्षर होने चाहिए।
5. यदि ठेकेदार कोटेशन देने से पहले कार्य का मुआइना करना चाहें तो वह अपने खर्च पर ऐसा कर सकते हैं।
6. कोटेशन के साथ निर्धारित बयाना राशि **8000/- का बैंक ड्राफ्ट/बैंकर चैक, जो आई.सी.ए. आर. युनिट, सी,पी,आर,आई, शिमला** के नाम बना हो, संलग्न होना चाहिए। बिना बयाना राशि के प्राप्त कोटेशन को मंजूर नहीं किया जाएगा।
7. उक्त कार्य आदेश मिलने की तिथि के 90 दिनों के भीतर पूरा करना होगा।

लगातार.....

8. यदि ठेकेदार या उनके कामगारों द्वारा संस्थान की प्रापर्टी को नुकसान पहुँचाया जाता है तो उस स्थिति में ठेकेदार को अपने खर्च पर उसकी भरपाई या मरम्मत करनी होगी। यदि ठेकेदार ऐसा करने में असमर्थ पाया जाता है तो उसकी भरपाई/मरम्मत का खर्च, ठेकेदार को किए जाने वाले भुगतान में से काट लिया जाएगा ।
9. ठेकेदार द्वारा कार्य आदेश मिलने के बाद सात दिनों के भीतर अपनी सहमति/मंजूरी इस कार्यालय में अवश्य देनी होगी ।
10. यदि ठेकेदार आबंटित कार्य को पूर्ण करने में असफल पाया जाता है तो उनके द्वारा जमा की गई ब्याना राशि को जब्त कर दिया जाएगा और भविष्य में उन्हें इस संस्थान द्वारा कोई भी कार्य नहीं दिया जाएगा ।
11. सभी प्रकार के किए जाने वाले कार्य का भुगतान, माल की मात्रा के अनुसार प्रभारी, अभियन्त्रण अनुभाग द्वारा ली गई पैमाइश या प्रभारी अधिकारी के आदेशों के अनुसार ही किया जाएगा ।
12. संस्थान के निदेशक के पास यह अधिकार सुरक्षित हैं कि वह बिना कारण बताए किसी भी कोटेशन को रद्द कर सकते हैं ।
13. यदि ठेकेदार द्वारा उक्त कार्य हेतु संस्थान का पानी इस्तेमाल किया जाता है तो उनके बिल से 1 प्रतिशत की कटौती की जाएगी ।

(अमर देव शर्मा)

प्रशासनिक अधिकारी (स्था-2)

संलग्न: उपरोक्त

To

The Admin. Officer (Estt-II)
Central Potato Research Institute,
Shimla.

Reference: Your quotation F.No.02-133/2015/Estt-II./..... dated -----
for “Repair of sewer line and retaining wall of Type-III (C-Block) at Green Park
colony Khalini, Shimla”-reg.

Sir,

Having examined your above mentioned quotation letter including details of work to be executed (DNIT), the receipt of which is hereby duly acknowledged, I, the undersigned offer to execute the above work in conformity with the said quotation document for the sum as shown against each item of work and at a total of Rs. _____.

I, hereby undertake if my quotation is accepted, to execute the work in accordance with the details of work, as specified in the details of work after fulfilling all the applicable requirements incorporated in the above referred quotations.

I agreed to abide by this quotation for the validity period specified or for the subsequently period, if any agreed to by me and it shall remain binding upon me and may be accepted at any time before the expiration of the period.

Until a formal contract work order is prepared and executed, this offer together with your written acceptance thereof and your notification of work award, shall constitute a binding contract between us.

I understand that you are not bound to accept the lowest or any bid you may receive.

Date : _____

Place : _____

(Signature of the contractor)
With name, address,
seal
and registration No. _____

Description of work

Name of work-: Repair of sewer line and retaining wall of type-III (C-Block) at Green Park colony ,Khalini, Shimla .

SN	Detail of work	Quantity	Unit	Rate	Amount(Rs)
1	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 meter lead (A) For thickness of tiles 10 mm to 25 mm	50.00 m2	Sqm		
2	Demolishing cement concrete manually / by mechanical means including disposal of material with in 50 m lead as per direction of Engineer in charge . (A) Nominal concrete 1:3:6 or richer mix	1.00 m3	cum		
3	Demolishing stone rubble masonry manually / by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 meter lead as per direction of Engineer-in-charge (A) In cement mortar	10.0 m3	cum		
4	Earth work in excavation by mechanical means(Hydraulic excavator) / manual means in foundation trenches or drain (not exceeding 1.5 m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms , lift up to 1.5 m , including getting out the excavated soil as directed , with in a lead of 50 m. (All kinds of soil .	30.00 m3	cum		
5	Providing and laying in position cement concrete of specified grade excluding the cost of centering ad shuttering -All work up to plinth level				
5A	1:5:10 (1 cement : 5 coarse sand :10 graded stone aggregate 40 mm nominal size)	7.00m3	cum		
5B	1:2:4 (1 cement : 2 coarse sand :4 graded stone aggregate 20 mm nominal size)	1.00 m3	cum		
6	Constructing brick masonry manhole in cement mortar 1:4 (1 cement :4 coarse sand) with R.C.C. top slab with 1:2:4 mix(1 cement : 2 coarse sand :4 graded stone aggregate 20 mm nominal size) foundation concrete 1:4:8(1 cement : 4 coarse sand :8 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1cement :3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4(1 cement : 2 coarse sand :4 graded stone aggregate 20 mm nominal size) finished with a floating coat of neat cement complete as per standard design (A) Inside size 90x80cm and 90 cm deep including C.I. cover with frame (light duty) 455x610	5 No	each		

	mm internal dimensions , total weight of cover and frame not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg) with common burnt clay F.P.S. (non modular) bricks of class designation 7.5				
7	Constructing brick masonry road gully chamber 50x45x60 cm with bricks in cement mortar 1:4 (1 cement :4 coarse sand) including 500x450 mm pre-cast R.C.C. horizontal grating with frame complete as per standard design (A) With common burnt clay F.P.S. (non modular) bricks of class designation 7.5	2 No	each		
8	Providing and fixing soil ,waste and vent pipes (A) 100 mm dia, Sand cast iron S&S pipes as per IS:1729	50.0 mtr	meter		
9	Providing and fixing bend of required degree with access door , insertion rubber washers 3 mm thick , bolts and nuts complete . (A) 100 mm dia, Sand cast iron S&S pipes as per IS:1729	1 No	each		
10	Providing and fixing plain bend of required degree (A) 100 mm dia, Sand cast iron S&S pipes as per IS:1729	2 No	each		
11	Providing and fixing double equal plain junction of required degree (A) 100x100x100x100 mm , Sand cast iron S&S pipes as per IS:1729	2 No	each		
12	Providing and fixing collar (A) 100 mm dia, Sand cast iron S&S pipes as per IS:1729	8 Nos	each		
13	Providing lead caulked joint to sand cast iron / centrifugally cast (spun) iron pipes of diameter (A) 100 mm	15 Nos	each		
14	Centering and shuttering including strutting , propping etc and removal of form for (a) Lintels , beams , plinth beams , girders , bressumers and cantilevers	5.0 m2	sqm		
15	Steel reinforcement for R.C.C. work including straightening , cutting , bending , placing in position and binding all complete up to plinth level (a) Cold twisted bars	75.0 Kg	kg		
16	Reinforcement cement concrete work in beams , suspended floors , roofs having slop up to 15 degree , landing , balconies , shelves , chajjas , lintels bands , plain window sills , staircase , and spiral staircase up to floor V level excluding the cost of centering and shuttering , finishing and reinforcement with 1:2:4 (1 cement : 4 coarse sand : 4 graded stone agg. 20 mm nominal size)	1.0 m3	cum		
17	15 mm cement plaster on the rough sides of single or half brick wall of mix 1:4 (1 cement : 4 fine sand)	40.00 m2	sqm		

18	Extra depth of manholes size 90x80 with burnt clay F.P.S. (non modular) bricks of class designation 7.5	5.0 meter	meter		
19	Dismantling of manhole including R.C.C. top slab ,C.I. cover with frame , including stacking of useful material near the site and disposal of unserviceable materials into municipal dumps with in 50 m lead .(A) Rectangular manhole 120x90cm and 90 cm deep	5 No	each		
20	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in cement mortar 1:6 (1 cement :6 coarse sand)	7.50 m3	cum		
21	Chequerred precast cement concrete tiles 22 mm thick in footpath & courtyard , jointed with neat cement slurry mixed with pigment to match the shade of tiles , including rubbing and cleaning etc complete , on 20 mm thick bed of cement mortar 1:4 (1cement : 4 coarse sand) . (A) Ordinary cement without any pigment	50.0 m2	sqm		
22	Random rubble masonry with hard stone in superstructure above plinth level and up to floor V level , including leveling up with cement concrete 1:6:12 (1 cement :6 coarse sand :12 graded stone aggregate 20 mm nominal size) at window sills ,ceiling level and the like (A)Cement mortar 1:6 (1 cement : coarse sand)	10.00 m3	cum		
	Total amount (figures)				
	Total amount (words)				

Term and Conditions-

- (1) No electricity will be provided by the Institute.
- (2) All dismantled material should be disposed at the dumping site of Municipal Corporation out of the CPRI campus. No extra payment will be made for the disposing the above material.

Name & Address of Contractor

